

DIMENSIONS

Tab.1 Thin-weight (type L1), EN 10255, UNI 8863, STAS 7656

DN	Connecting nominal width of the fittings	OD			WT [mm]
		<i>nom</i> [mm]	<i>min</i> [mm]	<i>max</i> [mm]	
15	1/2	21.3	21.0	21.7	2.3
20	3/4	26.9	26.4	27.1	2.3
25	1	33.7	33.2	34.0	2.9
32	1 1/4	42.4	41.9	42.7	2.9
40	1 1/2	48.3	47.8	48.6	2.9
50	2	60.3	59.6	60.7	3.2
65	2 1/2	76.1	75.2	76.3	3.2
80	3	88.9	87.9	89.4	3.6
100	4	114.3	113.0	114.9	4.0

Tab. 2 Medium-weight (type M), EN 10255, DIN 2440, STAS 7656

DN	Connecting nominal width of the fittings	OD			WT [mm]
		<i>nom</i> [mm]	<i>min</i> [mm]	<i>max</i> [mm]	
15	1/2	21.3	21.0	21.8	2.6
20	3/4	26.9	26.5	27.3	2.6
25	1	33.7	33.3	34.2	3.2
32	1 1/4	42.4	42.0	42.9	3.2

40	1 1/2	48.3	47.9	48.8	3.2
50	2	60.3	59.7	60.8	3.6
65	2 1/2	76.1	75.3	76.6	3.6
80	3	88.9	88.0	89.5	4.0
100	4	114.3	113.1	115.0	4.5

Tab.3 Heavy-weight (type H), EN 10255, DIN 2441, STAS 7656

DN	Connecting nominal width of the fittings	OD			WT [mm]
		<i>nom</i> [mm]	<i>min</i> [mm]	<i>max</i> [mm]	
15	1/2	21.3	21.0	21.8	3.2
20	3/4	26.9	26.5	27.3	3.2
25	1	33.7	33.3	34.2	4.0
32	1 1/4	42.4	42.0	42.9	4.0
40	1 1/2	48.3	47.9	48.8	4.0
50	2	60.3	59.7	60.8	4.5
65	2 1/2	76.1	75.3	76.6	4.5
80	3	88.9	88.0	89.5	5.0
100	4	114.3	113.1	115.0	5.4